

## Invertec 135S, 150S, 170S

Inventory pre  
zváranie obalenou  
elektrodou



	Invertec 135S	Invertec 150S	Invertec 170S
Priemer elektródy (mm)	1,5 - 3,2	1,5 - 3,2	1,5 - 4,0
Rutilová/bázická elektróda	x	x	x
Hot Start		x	x
Arc Force		x	x
Soft a Crisp režim		x	x
Arc Control	x	x	x
Anti Stick	x	x	x
Max. dĺžka káblov	30 m	60 m	60 m
Použitie elektrocentrály		x	x
Lift TIG	škrtanie	Lift TIG	Lift TIG
Digitálny displej			x
Ventilátor		x	x
Záruka	2 roky		

Typ	Kód produktu	Napájanie	Istenie (A)	Zaťaženie (20 )	Zaťaženie (40 )	Hmotnosť (kg)	Rozmery v x š x d (mm)	Trieda ochrany
Invertec 135S	K12033-1	230V/1 fáza/50-60Hz	16 A	120A pri 50%	120A pri 25%	4,6 kg	224 x 148 x 315	IP 21
Invertec 150S	K12034-1	230V/1 fáza/50-60Hz	16 A	140A pri 55%	140A pri 30%	6,7 kg	244 x 148 x 365	IP 23
Invertec 170S	K12035-1	230V/1 fáza/50-60Hz	16 A	160A pri 80%	160A pri 35%	7,0 kg	244 x 148 x 365	IP 23