

## A CUT ABOVE THE REST

## Outside clamping tube and fittings facing machine type SE 25 RA



The portable machine SE 25 RA is specially designed for facing in position the diameters from 2 mm to 25,4 mm **under tight places of work**.

The tool holder plate equipped with one tool insert allows to cover the machining range without any adjustment.

The set up of the tube is carried out quickly through a stainless steel monobloc collet.

The machine features a graduated vernier which gives a high quality and accurate weld prep.

## **TECHNICAL FEATURES:**

Machining capacity:	2 mm OD – 25,4 mm OD	125 mm	
Clamping capacity:	5/64" OD – 1" OD 2 mm OD – 25,4 mm OD 5/64" OD – 1" OD		
Clamping: Feed:	manual, with clamping lever Graduated manual feed 1 div. = 0,1 mm /0.004"		
Weight: Dimensions: RPM:	2,5 kg please see drawing Level 1: 0 – 400 rpm Level 2: 0 – 1250 rpm		
Drive:	cordless electric drive 12 V / 1,4 Ah		320 mm
Optional equipment:	SE 65 for Ø 12,7 - 63,5 mm OD Ø $1/2^{\circ} - 2 1/2^{\circ}$ additional clamping head for angled ends of tubes SE25 standard version with in lin electric drive		
Expansion collets:	<ul> <li>for inch. diameters</li> <li>for mm diameters</li> <li>extra short collets for Microfittin</li> </ul>	ngs	

Subject to technical modification without prior information !



Am Hambiegel 27 D - 76706 Dettenheim Telefon: + 49-(0) 72 47-93 93-0 Telefax: + 49-(0) 72 47-94 68 62 e-mail: Protem-gmbh@t-online.de



110