

A CUT ABOVE THE REST

Tube Facing Machine for Tubesheets type US 18 TP



The US 18 TP is a fully automatic driven with an integrated control box. It features a machine positioning limit-stop and a machining limit-stop.

This machine allows to perform all types of bevels, tube facing and tube/tubesheet removal, weld excavation for instance:

• outcoming tubes from tube plates can be cut/shorted for instance on steam generators.

- prepare tubes ends automatically with a weld prep.
- remove already existing welds on boiler tubes.

The tube-preparation is simple: the operator pushes the clamping head into the tube. Through a pressure on the integrated button for the function "on", the machine will clamp itself automatically; the milling head begins to rotate and moves itself in the axial direction. Adjustable limit stops lay down the beginning and the end of the preparation.

TECHNICAL FEATURES:

Machining capacity:	max \varnothing 36 mm (Standard) max \varnothing 23 mm (Special mandrel)
Clamping capacity:	18 - 30 mm ID (Standard) 12 - 17 mm ID (Special mandrel)
Clamping:	pneumatic, automatic
Expansion:	2 mm
Feed:	max 20 mm, pneumatic, automatic, with limit stop. Adjustable speed.
Weight:	6 kg
Dimensions:	see back of the data sheet
RPM:	Off-load speed: 300 rpm Nominal speed: 150 rpm

Drive: Power: working pressure: Air intake: Tooling: pneumatic drive 370 Watt 6 bar 350 I/min quick changing milling head (one per diameter) with carbide inserts

Optional equipment:

- Balancer
- Special mandrel 12 17 mm (one per diameter)
- Special clamping heads on request.

This machine must be equipped with a lubricating filter !

Subject to technical modification without prior modification !

For works with larger diameters: US 25 TP. Please call Protem!



Am Hambiegel 27 D - 76706 Dettenheim Telefon: + 49-(0) 72 47-93 93-0 Telefax: + 49-(0) 72 47-94 68 62 e-mail: Protem-gmbh@t-online.de





A CUT ABOVE THE REST

Dimensions:





Am Hambiegel 27 D - 76706 Dettenheim Telefon: + 49-(0) 72 47-93 93-0 Telefax: + 49-(0) 72 47-94 68 62 e-mail: Protem-gmbh@t-online.de

